

"Accessory Options"

Optional Internal Lens or Shielding (Up to Two can be Specified)

4 1/2" 2 3/4" 1 3/8" 2 1/2" Dia. 5/8" 1 5/8" Locking O-Ring Compression Knuckle 1/2" Pipe Thread

Cutoff Visor

Cutoff Snoot

Adj. Barn Doors

Spot

Flood

Wall Wash

EXAMPLE: SA - SP - 20 - VER - 9 - 11 - BD

Series:

Optics:

SP - Spot
FL - Flood
WW - Wall Wash

Lamp Type:

0 - By Others
20 - Q20T4/CL-12V(20W)
64 - Q35T4/CL-12V(35W)
65 - Q50T4/CL-12V(50W)

Finish:

Powdercoat	Satin	Wrinkle
Bronze	B2P	B2W
Black	BLP	BLW
White (Gloss)	WHP	WHW
Aluminum	SAP	VER

Lens Type:

9 - Clear (Standard)
10 - Spread
13 - Rectilinear

Shielding:

11 - Honeycomb Baffle

Accessories:

CV - Cutoff Visor
CS - Cutoff Snoot
BD - Adjustable Barn Doors

Features:

- All Precision Machined Aluminum Construction.
- Locking O-Ring Compression Knuckle (THE L.O.C.K.) Allows Vertical to Horizontal Aiming and Provides Integral, Sealed Wireway.
- T4 Lamp Holder With 260°C, 18 Ga. Wire Leads (Leads Extend 6" Beyond Mounting Knuckle).
- Utilizes any T4 Lamp Up To 50 Watts.
- Gasketed End Caps, Forms Rainlight Optical Compartment With Clear, Tempered, Glass Lens, Factory Sealed.
- Polyester Powdercoat Finishes Standard. (Specify).

"Optics"

See OPTIKIT™ Submittal Sheet for Field Interchangeable Optics Ordering Information.

ETI LIMITED
CONFORMS TO AMERICAN
STANDARD TEST AND IS SUBJECT 1750
CERTIFIED TO CANADIAN
STANDARD C22.2 NO. 1.

CEC **UL** **US**

SARATOGA SERIES™

6/03 **B-K LIGHTING, INC.** DRAWING NUMBER
SUB-1202-02

FRONT ELEVATION

4" 2'-2" 4" 1'-3" 3'-8" 1'-5"

1/4" TEMP. GLASS -CLEAR

CRYSTAL CHANDELIER FIXTURE INSIDE WATER TIGHT BOX

SIDE ELEVATION

6'-4" 2'-2"

1/4" TEMP. GLASS -CLEAR

1" FLAT METAL 'X'

ONLY TOP AND SIDES RECEIVE 1" FLAT METAL 'X'

PLAN

6" 2'-2" 2'-2"

UL RATED CRYSTAL CHANDELIER LGTH FIXTURE INSIDE WATER TIGHT GLASS BOX

INSPIRED BY THE OPULENCE OF VICTORIAN ENGLISH CHANDELIERS, OUR PERFECTLY PROPORTIONED DESIGN MIXES RUSTIC IRON WITH A PROFUSION OF CRYSTAL, PRECISION-CUT AND POLISHED FOR OPTIMAL REFRACTION AND SPARKLE.

RUSTIC IRON FRAMEWORK LENDS AUTHENTICITY ANTIQUED RUST AND MATTE LACQUER FINISH STRUNG WITH HUNDREDS OF LIGHT-REFRACTING CRYSTALS CURVED ARMS RAISE CANDLESTICK-STYLE SOCKETS CRYSTAL DROPS HANG BELOW THE METAL ARMS USES EIGHTEEN 40W MAX. CANDELABRA BULBS

Precision
MR-16 - Remote Transformer - Offset (RD)

	PROJECT:
	TITLE:
	CATALOG NUMBER:
	LA/HP/PS:
	NOTES:

CATALOG NUMBER LOGIC

CO2

OS

MR

RD

33

BZP

13

AH

Example B - CO2 - OS - MR - RD - 6 - POL - 12 - AH

Material
Blank - Aluminum B - Brass S - Stainless Steel

Faceplate
COS - Flange

Style
OS - Offset Lens

Optilock®
MR - MR-16

Housing
RD - Requires Remote Transformer

Lamp Type

0 - Bay Others	4 - FRA (25W) 12" H Flood	17 - EYE (25W) 40" Flood	9 - FRV (50W) 60" W Flood
1 - ETC (20W) 12" Spot	5 - FAW (250W) 6" Flood	8 - ECT (20W) 12" Spot	33 - EYE (50W) 12" Spot
2 - BMS (20W) 40" Flood	15 - FRV (40W) 12" Spot	7 - EZE (50W) 20" H Flood	33 - EYE (50W) 20" H Flood
3 - FES (10W) 12" Spot	16 - EYE (30W) 32" W Flood	8 - EYE (50W) 40" Flood	34 - EYE (50W) 40" Flood

Finish

Aluminum & Brass Faceplates		Brass Faceplates	
Powder Coat Color	Surfin	Winkon	
Bronze	BZP	BZW	MAC
Black	BLP	BLW	Nitroque™ INT
White (Gloss)	WHP	WHW	
Aluminum	NAP	---	POL
Verde	---	VER	brushed BRU

Also available in Premium Finishes. See submittal 506-129 for Premium Finishes.

Accessory Select up to 2. Requires Accessory Hub Drive.

10 - Spread Lens	11 - Honeycomb Baffle	12 - Soft Focus Lens	13 - Rectilinear Lens
------------------	-----------------------	----------------------	-----------------------

Option

AH - Accessory Hub for Programmable up to 2 axial
DS - Dims & Lens Locks (See Data, see Dimmer Switch)

BK No	Lamp Watts	Description	Rated Life	Center Beam Candlepower	BK No	Lamp Watts	Description	Rated Life	Center Beam Candlepower
1	20	ESS	4,000	2,000	8	50	EXS	5,000	9,500
2	20	RAB	4,000	500	7	50	EXN	5,000	3,250
3	35	FRB	5,000	7,600	8	50	EXN	5,000	1,800
4	35	FRW	5,000	2,300	9	50	FNV	5,000	700
5	35	FRW	5,000	1,100	32	75	EYF	3,000	12,700
15	42	EYB	5,000	1,300	33	75	EYD	5,000	4,400
16	42	EYB	5,000	2,800	34	75	EYD	5,000	2,200
17	42	EYV	5,000	1,100					

B-K LIGHTING	40429 Brickyard Drive • Modesto, CA 95638 • USA 559.439.5800 • FAX 559.438.8800 www.bklighting.com • info@bklighting.com	SUBMITTAL DATE 10-19-10	DRAWING NUMBER SUB-1373-00
---------------------	---	----------------------------	-------------------------------

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF B-K LIGHTING, INC. AND ITS REGENT OR POSSESSOR DOES NOT TO COPY ANY RIGHTS TO REPRODUCE, DISCLOSE ITS CONTENTS, OR TO MANUFACTURE, USE OR SELL ANYTHING IT MAY BE DESCRIBED HEREIN, UNDER OR OTHERWISE WITHOUT THE WRITTEN PERMISSION OF B-K LIGHTING, INC. © 2010 B-K LIGHTING, INC.

Precision

MR-16 - Remote Transformer - Offset (RD)

CO2

SIDE VIEW

7 1/2" Dia

3 1/8" Dia

14 1/2"

1/8"

Patented stability Range

Patented Power-Locker Barrier Plate Assembly (ACV™)

4" Dia

PROJECT:	
TYPE:	

FACEPLATE

TOP SIDE VIEW

1/8"

1/8"

BOTTOM VIEW

2 1/8"

[illegible]

Pracicki,® and its features are covered in whole or in part by U.S. Patent Nos. 7,093,038; 6,254,256 B1; 7,240,867 B2; 7,370,968 B2; 7,553,032; 7,560,148; and 7,609,489.

Restoration Hardware

12.23.2011

© 2008 NELSEN PARTNERS, INC.

Project No.
31185