Drainage Reports

Abbreveated Water & Sewer Need Reports

Water Study

Wastewater Study

Stormwater Waiver Application

WASTEWATER DISTRIBUTION SYSTEM BASIS OF DESIGN REPORT

FOR

DIVERSIFIED PARTNERS-MULTI-FAMILY PROJECT

3440 & 3450 E. McDonald Drive SCOTTSDALE, ARIZONA

OWNER:

DIVERSIFIED PARTNERS, LLC 7500 E. MCODNALD DRIVE STE. 100A SCOTTSDALE, AZ 85250 480.947.8800

> December 19, 2016 Revised: March 16, 2017



PREPARED BY:

JACOBS WALLACE, LLC 2233 W. Bethany Home Rd. Phoenix, AZ 85015 602.757.5964

F, le

TABLE OF CONTENTS

INTRODUCTION	1
EXISTING CONDITIONS	1
PROPOSED CONDITIONS	1
SUMMARY	1

Appendix:

Vicinity Map
Calculations
Preliminary Design
City of Scottsdale Quarter Section Map

INTRODUCTION

The proposed project consists of a multi-story multi-family building with associated site improvements. The existing conditions include 2-delapidated buildings with associated site improvements sitting on 2 lots. The lots would be combined into one with the proposed project. The 1.085-acre site is located just west of Granite Reef Rd on the north side of McDonald Dr. The site is bordered to the north and west by an existing multi family development, to the east by existing commercial development, to the south by McDonald Drive. The site lies within the Southwest Quarter of Section 12, Township 2 North, Range 4 East of Gila and Salt River Base and Meridian. See the Appendix for a vicinity map.

EXISTING CONDITIONS

There is an existing 15" VCP sewer main within McDonald Dr. There are services from this main to each existing lot. The existing services will not be utilized for this project.

PROPOSED CONDITIONS

The proposed project will install a new 6" private sewer to service the project. There will be a new 6" sewer connection made within a new manhole on the existing 15" sewer within McDonald Dr. The proposed sanitary sewer system will consist of a new private 6" line serving the project at 1% minimum slope. The existing sewer services will be capped and abandoned at the right of way line of McDonald Dr.

The private sewer line construction and design will conform to Uniform Plumbing Code.

WASTEWATER ANALYSIS

Number of Units: 25 (3-bedroom assumed)

Unit Daily Flows:

3 Bedroom = 400 gpd

Average Daily Flow:

25*400gpd = 10,000 gpd

Peak Daily Flow:

10,000 gpd * 4.5 = 45,000 gpd = 31.25 gpm

SUMMARY

A 6" line with a slope of 1.0% flowing at 75% full carries 229 gpm with a velocity of 3.2 fps. A 6" line carrying 32 gpm flows with a velocity of 2.0 fps. See attached calculations in the Appendix. These parameters fall within acceptable ranges as set forth in the City of Scottsdale guidelines.

APPENDIX

Manning Pipe Calculator


75% FULL


Given Input Data:	
Shape	Circular
Solving for	
Diameter	
Depth	4.5000 in
Slope	
Manning's n	
Computed Results:	
Flowrate	229.6492 gpm-US
Area	
Wetted Area	0.1580 ft2
Wetted Perimeter	12.5664 in
Perimeter	18.8496 in
Velocity	3.2391 fps
Hydraulic Radius	1.8101 in
Percent Full	
Full flow Flowrate	251.8421 gpm-US
Full flow velocity	2.8577 fps
Critical Info	rmation
Critical depth	4.5680 in
Critical slope	
Critical velocity	
Critical area	
Critical perimeter	12.5609 in
Critical hydraulic radi	
Critical top width	
Specific energy	0.5443 ft
Minimum energy	
Froude number	
Flow condition	Supercritical

Manning Pipe Calculator

PEAK FLOW

Given Input Data:
Shape Circular
Solving for Depth of Flow
Diameter 6.0000 in
Flowrate 32.0000 gpm-US
Slope 0.0100 ft/ft
Manning's n 0.0130
Computed Results:
Depth 1.4443 in
Area 0.1963 ft2
Wetted Area 0.0364 ft2
Wetted Perimeter 6.1538 in
Perimeter 18.8496 in
Velocity 1.9592 fps
Hydraulic Radius 0.8515 in
Percent Full 24.0719 %
Full flow Flowrate 251.8421 gpm-US
Full flow velocity 2.8577 fps
Critical Information
Critical depth 1.5751 in
Critical slope 0.0071 ft/ft
Critical velocity 1.7340 fps
Critical area 0.0411 ft2
Critical perimeter 6.4552 in
Critical hydraulic radius 0.9172 in
Critical top width 5.2800 in
Specific energy 0.1800 ft
Minimum energy 0.1969 ft
Froude number 1.1839
Flow condition Supercritical





K8350 E. MCDONALD DRIVE SCOTTSDALE, AZ

8340

ACOBS WALLACE, LLC


Company of the compan



FEBRUARY 2017

DRAVING NO.

JDB: 0068



WATER DISTRIBUTION SYSTEM

BASIS OF DESIGN REPORT

FOR

DIVERSIFIED PARTNERS-MIXED USE PROJECT

3440 & 3450 E. McDonald Drive SCOTTSDALE, ARIZONA

OWNER:

DIVERSIFIED PARTNERS, LLC 7500 E. MCODNALD DRIVE STE. 100A SCOTTSDALE, AZ 85250 480.947.8800

> December 19, 2016 Revised: March 16, 2017



PREPARED BY:

JACOBS WALLACE, LLC

2233 W. Bethany Home Rd. Phoenix, AZ 85015 **602.757.5964**

F.ll

TABLE OF CONTENTS

INTRODUCTION	1
EXISTING CONDITIONS	1
PROPOSED CONDITIONS	1
SUMMARY	1
CONCLUSION	2

Appendix: Vicinity Map Calculations Flow Test Results City of Scottsdale Quarter Section Map Preliminary Design Plan

INTRODUCTION

The proposed project consists of a multi-story multi-family building with associated site improvements. The existing conditions include 2-delapidated buildings with associated site improvements sitting on 2 lots. The lots would be combined into one with the proposed project. The 1.085-acre site is located just west of Granite Reef Rd on the north side of McDonald Dr. The site is bordered to the north and west by an existing multi family development, to the east by existing commercial development, to the south by McDonald Drive. The site lies within the Southwest Quarter of Section 12, Township 2 North, Range 4 East of Gila and Salt River Base and Meridian. See the Appendix for a vicinity map.

EXISTING CONDTIONS

There is an existing 6" water line in McDonald Drive that is stubbed approximately 85' west of the western edge of the proposed project. Currently there are 2-1" meters and service connections that service the exiting buildings that will be abandoned. These services extend over to the 6" water main west of the property.

PROPOSED CONDITIONS

The project is proposing to extend an 8" public waterline across the frontage of the property within McDonald Drive and connect to the Granite Reef waterline. Construction of the proposed offsite waterline will include stubs to the property as a part of the water main extension. There will be 2-6" fire hydrant line services, 1 domestic service connection and master meter, and a landscape service connection and meter stubbed to the proposed property. There will be backflow preventers associated with each service. The project will be services by private waterlines and private sub meters. There will be a master public meter for the site and then private waterline services to each unit with private sub-meters at each unit.

All water line construction and design will conform to M.A.G. standards and specifications and the latest revision of the <u>City of Scottsdale Design Standards and Policies Manual</u>. All water demands are based on Figure 4.1-3, Average Day Water Demand per Dwelling Unit of the <u>City of Scottsdale Design Standards and Policies Manual</u>. The offsite waterline construction will be reimbursable by agreement with the City after completion of construction.

WATER ANALYSIS

Number of Units: 25

Average Daily Demand: 185.3 gpd/unit

25 units * 185.3gpd/unit = 4,633gpd = **3.2gpm**

Maximum Daily Demand: Average Daily Demand x 2

4,633gpd*2=9,266gpd = 6.4 gpm

Peak Demand: Maximum Daily Demand x 3.5

9,266gpd*3.5 = 32,431gpd = **22.5**gpm

Fire Flow Demand: (Per City of Scottsdale DSPM Section 6-1.501)

1,500 gpm @ 30 psi (For commercial, industrial, and multi-family)

Max Daily Demand + Fire Flow = 1,510 gpm @ 30 psi (COS requirement)

WATER MODEL RESULTS

A water model was completed based on the City of Scottsdale requirement of 1,500 gpm + Max daily demand at 30 psi. The water model simulated the design of the proposed waterline using the required flow of 1,510 gpm for the fire analysis scenario and 10gpm for the domestic demand scenario. As shown on the attached modeling results, when a demand of 1,510gpm is placed on the junctions J11 &J13 the available flows are 1,602 gpm and 1,618 gpm respectively with a residual pressure of 30 psi. Both of these flows are greater than the required 1,510 gpm at 30 psi per the City of Scottsdale requirements.


Please note the model is solely based on the current fire flow test. (See attached) The model is built from this point thru the new development. It is not modeled back to the water source, which would give more accurate results. The elevations are negligible on this site as the elevations differences are minimal.

CONCLUSION

Based on the information provided, the flow simulation indicates that the 6" waterline feeding the proposed onsite hydrant provides acceptable velocities, pressures and flows.

It is important to note that the actual available flow can be affected by varying seasonal and diurnal water demands, growth within the City, and system operations. This report solely describes the flow available at a design maximum day condition based on current flow tests.

APPENDIX



E·J Flow Test Summary

EJ Project ID:

16060

Project Address:

8355 E McDonald Dr. Scottsdale, AZ, 85250

Date of Flow Test:

2016-03-16

Time of Flow Test: Data Reliable Until: 8:34 AM 2016-09-16

Conducted By:

Austin Gourley (EJ Flow Test), Eder Cueva (EJ Flow Test), & John Echeverri (EJ Flow Test)

Witnessed By:

Phil Cipolla (City of Scottsdale) 602.828.0847

City Forces Contacted:

City of Scottsdale

Permit Number:

C50025

Raw Flow Test Data:

Static Pressure:

78.0 PSI

Residual Pressure:

50.0 PSI

Flowing GPM:

1.513

GPM @ 20 PSI:

2.242

Pitot Pressure One:

18 PSI

Hydrant Orifice Diameter:

4.0 inches

Coefficient of Discharge:

0.9

extra coefficient of 0.83 factored in for pumper outlet per NFPA-291

Data with a 10 % Safety Factor

Static Pressure:

70.2 PSI

Residual Pressure:


42.2 PSI

Flowing GPM:

1.513

GPM @ 20 PSI:

2,074





Static-Residual Hydrant



Flow Hydrant

Distance Between Hydrants 217 ft (measured linearly)

Static-Residual Elevation 1271 ft (above sea level)

Flow Hydrant Elevation 1274 ft (above sea level)

Elevation & distance values are approximate

E·**J** Flow Test Summary

Static-Residual Hydrant:




Flow Hydrant:




Approximate Project Site:



Water Supply Curve:



Scenario: Base



Title: Hudson East c:\...\0037 - 83rd & mcdonald\dwg\project1.wcd 08/23/16 03:17:06 PM

Jacobs © Haestad Methods, Inc. 37 Brookside Road Waterbury, CT 06708 USA +1-203-755-1666

Project Engineer: C. Jacobs WaterCAD v7.0 [07.00.027.00] Page 1 of 1

Scenario: Base Fire Flow Analysis Fire Flow Report


Label	Satisfies Fire Flow Constraints?	Needed Fire Flow (gpm)	Available Fire Flow (gpm)	Total Flow Available (gpm)	Calculated Residual Pressure (psi)	Minimum Pressure (psi)
J-1	true	1,510.00	1,935.68	1,935.68	30.00	77.95
J-2	true	1,510.00	1,883.95	1,883.95	30.00	77.95
J-10	true	1,510.00	1,712.31	1,712.31	30.00	77.95
J-3	true	1,510.00	1,693.16	1,693.16	30.00	77.95
J-12	true	1,510.00	1,686.97	1,686.97	30.03	77.95
J-14	true	1,510.00	1,661.63	1,661.63	30.00	77.95
J-4	true	1,510.00	1,632.19	1,632.19	30.00	77.95
J-13	true	1,510.00	1,618.45	1,618.45	30.00	77.95
J-11	true	1,510.00	1,602.82	1,602.82	30.00	77.95
J-9	true	1,510.00	1,599.29	1,599.29	30.02	77.95
J-5	true	1,510.00	1,584.21	1,584.21	30.02	77.95
J-8	true	1,510.00	1,562.49	1,562.49	30.01	77.95
J-7	true	1,510.00	1,539.51	1,539.51	30.01	77.95
J-6	true	1,510.00	1,537.98	1,537.98	30.01	77.95

Scenario: Base Fire Flow Analysis Pipe Report

Label	From Node	To Node	Length (ft)	Diameter (in)	Hazen- Williams C	Material	Downstream Calculated Pressure (psi)			Discharge (gpm)
P-1	R-1	PMP-1	1.00	48.0	140.0	Ductile Iron	-0.00	0.00	0.27	1,510.00
P-2	PMP-1	J-1	35.00	6.0		Asbestos Cement	47.97	50.07		1,510.00
P-3	J-1	J-2	31.00	6.0	140.0	Asbestos Cement	46.95	47.97		1,095.17
P-4	J-2	J-3	214.00	6.0	140.0	Asbestos Cement	39.86	46.95	12.43	1,095.17
P-6	J-4	J-5	635.00	8.0	140.0	Asbestos Cement	40.35	39.49	2.65	-414.83
P-7	J-5	J-6	375.00	6.0	140.0	Asbestos Cement	42.40	40.35	4.71	-414.83
P-8	J-6	J-7	129.00	6.0	130.0	Ductile Iron	43.21	42.40	4.71	-414.83
P-9	J-7	J-8	223.00	6.0	140.0	Asbestos Cement	44.44	43.21	4.71	-414.83
P-10	J-8	J-9	167.00	6.0	140.0	Asbestos Cement	45.35	44.44	4.71	-414.83
P-11	J-9	J-10	262.00	6.0	140.0	Asbestos Cement	46.79	45.35	4.71	-414.83
P-12	J-10	J-1	216.00	6.0	140.0	Asbestos Cement	47.97	46.79	4.71	-414.83
P-13	J-3	J-12	100.00	8.0	130.0	Ductile Iron	38.93	39.86	6.99	1,095.17
P-15	J-11	J-12	204.00	8.0	130.0	Ductile Iron	38.93	35.47	9.64	-1,510.00
P-14	J-12	J-14	115.00	8.0	130.0	Ductile Iron	39.11	38.93	2.65	-414.83
P-16	J-14	J-4	247.00	8.0	130.0	Ductile Iron	39.49	39.11	2.65	-414.83
P-17	J-13	J-14	29.00	6.0	130.0	Ductile Iron	39.11	39.11	0.00	0.00

Scenario: Base Fire Flow Analysis Pipe Report

Label	From Node	To Node	Length (ft)	Diameter (in)	Hazen- Williams C	Material	Downstream Calculated Pressure (psi)	Upstream Calculated Pressure (psi)		Discharge (gpm)
P-1	R-1	PMP-1	1.00	48.0	140.0	Ductile Iron	-0.00	0.00	0.27	1,510.00
P-2	PMP-1	J-1	35.00	6.0	140.0	Asbestos Cement	47.97	50.07	17.13	1,510.00
P-3	J-1	J-2	31.00	6.0	140.0	Asbestos Cement	46.99	47.97	12.18	1,073.35
P-4	J-2	J-3	214.00	6.0	140.0	Asbestos Cement	40.16	46.99	12.18	1,073.35
P-6	J-4	J-5	635.00	8.0	140.0	Asbestos Cement	39.59	38.64	2.79	-436.65
P-7	J-5	J-6	375.00	6.0	140.0	Asbestos Cement	41.85	39.59	4.95	-436.65
P-8	J-6	J-7	129.00	6.0	130.0	Ductile Iron	42.74	41.85	4.95	-436.65
P-9	J-7	J-8	223.00	6.0	140.0	Asbestos Cement	44.08	42.74	4.95	-436.65
P-10	J-8	J-9	167.00	6.0	140.0	Asbestos Cement	45.09	44.08	4.95	-436.65
P-11	J-9	J-10	262.00	6.0	140.0	Asbestos Cement	46.67	45.09	4.95	-436.65
P-12	J-10	J-1	216.00	6.0	140.0	Asbestos Cement	47.97	46.67	4.95	-436.65
P-13	J-3	J-12	100.00	8.0	130.0	Ductile Iron	39.26	40.16	6.85	1,073.35
P-15	J-11	J-12	204.00	8.0	130.0	Ductile Iron	39.26	39.26	0.00	0.00
P-14	J-12	J-14	115.00	8.0	130.0	Ductile Iron	38.22	39.26	6.85	1,073.35
P-16	J-14	J-4	247.00	8.0	130.0	Ductile Iron	38.64	38.22	2.79	-436.65
P-17	J-13	J-14	29.00	6.0	130.0	Ductile Iron	38.22	36.23	17.13	-1,510.00



ARTINE.
LY PROJECT
CDONALD DRIV
SDALE, AZ
V, G & D

TTC WALLACE, I

JACOBS





FEBRUARY 2017

DRAWING NO. C1.0

JUB: 0068

