

22-DR-2019
4/30/2019

LRV 5

Painted Steel - Black "Dark Engine" - LRV of 5%
Weathering Steel - Fully Patinaed - LRV of 8%
Weathering Steel - Initial Installation - LRV of 14%
1" Insulated Glass with Low-E Coating
Bronze Anodized Window and Entry Door Frames - LRV of 5%
Painted "Navajo White" Stucco - LRV of 33%
Copper Tubing to patina naturally to old penny brown

**Bentley Renovation
Chen + Suchart Studio**

22-DR-2019
4/30/2019

Data based on NFRC methodology using LBNL Window 6.3 software and represents center of glass values. CEN EN-410/673 data based on CEN methodology using WUFI 5.1 software. 1" (24.7mm) insulating glass unit with two pieces of 1/4" (6mm) glass and a 1/2" (12.7mm) airspace per NFRC unless noted. See literature or visit www.dunnedwards.com for additional values. This sample is for glass aesthetic only, the spacer used is not representative of commercial units.

DE6350 Dark Engine
LRV 5

DEC772 Navajo White
LRV 70

To reorder, visit dunnedwards.com
or call (888) DE PAINT (337-2468)

Binder 9

STIPULATION SET
RETAIN FOR RECORDS
APPROVED
8/15/19
DATE
Bm
INITIALS

DE6049 Chaps
LRV 8

STIPULATION SET
RETAIN FOR RECORDS
APPROVED
8/15/19
DATE
Bm
INITIALS

22-DR-2019
4/30/2019