

## Archaeological Resources

Airport Vicinity Development Checklist

Parking Study

Trip Generation Comparison

Parking Master Plan

# **RJ-100SC** Self-Contained Compactor/Container

#### **Dimensions and Specifications**

Specifications				
Charge Box Capacity				
[Mfr. Rating]	1.5 cu yd	1.15 m <sup>a</sup>		
[NWRA Rating]	1.32 cu yd	1.01 m³ 889mm x 1524mm		
Clear Top Opening	35"L x 60"W			
Performance Characteristics:				
Cycle Time	37 sec.	37 sec.		
Total Normal Force	36,300 lbs.	161 kN		
Total Maximum Force	45,200 lbs.	201 kN		
Normal Ram Face Pressure	20,9 psi	144 kPa		
Maximum Ram Face Pressure	25.9 psi	179 kPa		
Ram Penetration	6.5"	165mm		
Electrical Equipment:	NE STATE	States (19-21)		
Electric Motor 3/60/230-460	10 hp	7.5kW		
Electric Control Voltage	120 VAC	120VAC		
Panel Box Assembly				
UL® and CUL® Listed	Key Operated	120 VAC		
All Circuits Fused	3-Button Controls: Keylock Start, Stop,			
All Girguits Pasea	Reverse			
Hydraulic Equipment:				
Hydraulic Pump	10 gpm	38 L/min		
Normal Pressure	1850 psi	128 bar		
Maximum Pressure	2300 psi	159 bar		
Hydraulic Cylinder - Bore	5"	127mm		
- Rod	2.5"	64mm		

	RJ-100SC						WT.
30 cu yd 34 cu yd	20 ou uda	4'0"	3' 25%"	7' 41/8"	22' 13/16"	8' 8"	9,400 lbs. 🖌
	30 cu yus	1219mm	981mm	2238mm	6736mm	2642mm	4273 kg
	24 au uda	4'0"	3' 25%"	7' 4 <sup>1</sup> /8"	24' 2"	8' 8"	9,900 lbs.
	34 cu yus	1219mm	981mm	2238mm	7366mm	2261mm	4500 kg

\* Overall height with hydraulic tailgate raised: 16'6". Hoist should be equipped with selector valve (1500 psi minimum) in order to control hydraulic tailgate

\*\* Other lengths available. Call factory for details



Dimensions not shown: 8'41/s" (2543mm) Overall Width

Ground Roller Widths: 61 1/8" (1569mm) Inside Rollers 67 3/s" (1712mm) Roller Centers 72 1/8" (1851mm) Outside Rollers



You can add the Pandora Remote Monitoring System to many of our most popular compactors. For information about adding Pandora, please contact your Marathon salesperson.

#### **Compactor Rental and Leasing Programs Available**

For detailed specifications, recommendations, or free economic studies comparing various systems, contact Marathon Customer Care at 1-800-633-8974



### **Authorized Dealer:**



Marathon Equipment Company P.O. Box 1798 Vernon, AL 35592-1798 800.633.8974 www.marathonequipment.com

Sourcewell Contract #060612-ESG





7-ZN-2015#2 05/23/2019

Products must be used with safe practice and in accordance with said regulations and standards. © 2018 Marathon Equipment Company. All rights reserved. Printed in USA. | SWS-M00114-031016

Pictures in this literature are illustrative only. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Certified in compliance with ANSI standard Z245.2, applicable OSHA Regulations, and certified under WASTEC's Stationary Compactor Certification Program.