



GROUND FLOOR NOTES

- 1 ALL WALLS IN EDI DRIVE-IN TREATED WITH FRP OR WATER PROTECTED LIKE MATERIAL
- 2 3'X4'X4" CLEANOUT SUMP, PROVIDE HEAVY DUTY METAL GRATING OVER SUMP, HEIGHT TO ALIGN WITH TOP OF CONCRETE SLAB, REFER TO STRUCTURAL
- 3 COMBINATION EMERGENCY SAFETY SHOWER AND EYE WASH UNIT, REFER TO PLUMBING FOR WATER AND WASTE PIPING
- 4 10'-0" HIGH GALVANIZED CHAIN LINK FENCE ENCLOSURE TO BE PROVIDED AND INSTALLED BY GC.
- 5 3'-0"x7'-0" GALVANIZED CHAIN LINK SWING GATE WITH EXIT DEVICE AND LOCKSET TO BE PROVIDED AND INSTALLED BY GC.
- 6 ROOF DRAIN AND OVERFLOW DRAIN, REFER TO PLUMBING. PROVIDE COWS TONGUE.
- 7 EXTERIOR STAIRS
- 8 LEAD LINING ALONG WALL
- 9 INSTALL EXISTING SALVAGED SLIDING DOOR, FRAME AND HARDWARE AT NEW LOCATION.
- 10 INSTALL SURFACE MOUNTED (2 BIKE) STEEL LOOP BICYCLE RACK, LOCATED MINIMUM 50'-0" FROM BUILDING ENTRANCE. REFER TO DETAIL ON AS-003.
- 11 LINE OF BRIDGE ABOVE
- 12 CONCRETE WALKWAY, REFER TO CIVIL DRAWINGS
- 13 SES - FLUSH WITH BUILDING FACE, REFER TO ELECTRICAL
- 14 INSULATED MOTORIZED OVERHEAD DOOR. SEE DOOR AND FRAME SCHEDULE.
- 15 INSULATED HOLLOW METAL SERVICE DOOR AND FRAME. GROUT FRAMES SOLID. SEE DOOR AND FRAME SCHEDULE.
- 16 LANDSCAPE, REFER TO LANDSCAPE DRAWINGS
- 17 ELECTRICAL PANEL BOARDS, REFER TO ELECTRICAL DRAWINGS
- 18 MOTORIZED EQUIPMENT PALLET LIFT. BASIS OF DESIGN: AUTOQUIP DPL-144-0030 DOUBLE PANTOGRAPH 72"x106", 2,000LB CAPACITY MINIMUM PLATFORM, 144" MIN. VERTICAL TRAVEL DISTANCE. PROVIDE SAFETY GUARDS ON PLATFORM AND SAFETY ENCLOSURE AT GROUND LEVEL.
- 19 FULLY GROUTED CORES

WESTERN TECHNOLOGIES WAREHOUSE

1395 N Hayden Rd  
Scottsdale, AZ 85257

NOT FOR  
CONSTRUCTION

Project No:	1395
Date:	10/29/2021
Drawn By:	JWN
Reviewed By:	JAMMON
No:	Revision
	Date

Sheet Title:  
FLOOR PLAN -  
LEVEL 1

Sheet No:  
**A1-100**

1 FLOOR PLAN - LEVEL 1

scale 1/4" = 1'-0"