

# NIVEOUS - LED Pendant

PD-52307, PD-52310, PD-52313



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## PRODUCT DESCRIPTION

The perfect sphere.

## FEATURES

- Mouth blown etched opal glass provides even illumination
- Integral swivel for sloped ceiling
- Driver located in standard 4" junction box
- Three 12" and one 6" downrods included (additional downrods available)
- 2.95" x 1.88" x 1.14" universal driver (120V - 220V - 277V)
- Color Temperature: 3000K (2700K/3500K special order)
- CRI: 90
- Rated Life: 70,000 hours
- Supplied with 114" of wire

## SPECIFICATIONS

**Construction:** Aluminum with acrylic diffuser


**Input:** 120V - 277V

**Dimming:** 100% - 10% ELV


**Light Source:** High output LED

**Finish:** Brushed Nickel (BN), White (WT), Aged Brass (AB)


**Standards:** ETL/cETL, Damp location listed



**PD-52307**



**PD-52310**



**PD-52313**

\*Driver installs within junction box

## ORDER NUMBER

Model	Size	Watt	LED Lumens	Delivered Lumens	Finish
<b>PD-52307</b>	7"	10W	777	588	<b>BN</b> <i>Brushed Nickel</i>
<b>PD-52310</b>	10"	14W	906	685	<b>WT</b> <i>White</i>
<b>PD-52313</b>	13"	14W	906	715	<b>AB</b> <i>Aged Brass</i>

Example: **PD-52310-BN**

For 2700K option, add "-27"; 3500K add "-35" before the finish: **PD-52310-27-BN**

dweLED.com

Phone (800) 526.2588

Fax (800) 526.2585

**Headquarters/Eastern Distribution Center**

44 Harbor Park Drive

Port Washington, NY 11050

**Central Distribution Center**

1600 Distribution Ct

Lithia Springs, GA 30122

**Western Distribution Center**

1750 Archibald Avenue

Ontario, CA 91760



## Haylen RGB Spec Sheet



**Fixture Style:**

Haylen RGB - Waterproof Outdoor Wall Light  
RGB Variant

**Dimensions:**

Length: 12" / 30 cm - 94" / 240 cm - 90W

Width: 2" / 5 cm

Depth: 1.8" / 4.5 cm

**Light Emitting:**

Pink, Yellow, Red, Blue Green, Purple and  
White colors with 358 Light Effects (Controlled  
via RF Wireless Remote)

**Installation:**

Mounting Style – Wall Mount (Hard-Wired)

**Certification/Ratings:**

UL, CCC, CE, CQC, EMC, FCC, GS, LVD, PSE, ROHS,  
SAA, and VDE; IP65 Waterproof Rating

**Other Specifications:**

Watts: 9W – 70W

Lumens: 1W = 100 lumens

Light Source: LED Bulbs

Voltage: 110V-240V

Power Source: AC

