

FIXTURE: S6

Table with columns: Project, Catalog #, Type, Prepared by, Notes, Date



McGraw-Edison TT TopTier

Parking Garage Luminaire

Product Features

Product Certifications



Connected Systems


- WaveLinx Lite
Synapse

- Quick Facts
Lumen packages range from 2,757 - 22,831
Efficacies up to 146 lumens per watt
Utilizes patented waveguide technology for maximum visual comfort
Surface, pendant, trunion, wall and direct conduit mount options

Dimensional Details

SURFACE MOUNT
CQ, MQ, WQ and RW: D1-D6
DL: D1-D4
Base luminaire weight: 18.2 lbs (8.3 kg)

SURFACE MOUNT
CQ, MQ, WQ and RW: D7+
DL: D5+
Base luminaire weight: 20.1 lbs (9.1 kg)



NOTES:
1. See McGraw-Edison.com for product details to confirm specifications. Not all product variations are D1C qualified.
2. DA Certified for 3000K CCT and warmer only.



PS513001EN page 1
February 26, 2024 6:31 PM

McGraw-Edison TT TopTier

Table with columns: Product Family, Configuration, Light Output, Color, Voltage, Distribution, Mounting, Finish


Table with columns: Product Family, Configuration, Light Output, Color, Voltage, Distribution, Mounting, Finish

- Notes:
1. See Light Connectors Qualified. Refer to www.designlights.org Qualified Products List under Family Models for details.
2. Only use with 48V IP66 systems. For NEC, see use with underground systems, impedance grounded systems and other grounded systems (generally known as Three Phase Three Wire Delta, Three Phase High Leg Delta and Three Phase Corner Grounded Delta systems).
3. Not available with 0-10V dimming.
4. Only for use with 48V IP66 systems. For NEC, see use with underground systems, impedance grounded systems and other grounded systems (generally known as Three Phase Three Wire Delta, Three Phase High Leg Delta and Three Phase Corner Grounded Delta systems).
5. IP66 ambient operating temperature: 0°C to 50°C (32°F to 122°F), 0°C to 35°C (32°F to 95°F). Not available with 0-10V dimming in 0-10V systems.
6. Ambient operating temperature: 0°C to 50°C (32°F to 122°F), 0°C to 35°C (32°F to 95°F). UL94V-0 rated components.
7. Includes integral photonic.
8. Designed for use with Dim Mount and Decorative Pendant Mount only.
9. Designed for use with Decorative Pendant Mount only.
10. Not available with 0-10V dimming or compatible with MS/DM or LRM sensors.

Product Specifications

- Construction
Low profile, die-cast aluminum housing provides a clean, symmetric aesthetic
Greater than 90% lumen maintenance at 50,000 hours
IP66 rated
120-277V 50/60Hz, 347V 60Hz or 480V 60Hz operation
Five optical distributions utilizing visual comfort waveguide technology
10 lumen packages, ranging from 2,757 to 22,831
Integral uplight optics utilizes a dedicated, RW light engine, producing 300 lumens for reduced visual contrast and glare
IDA Certified for 3000K CCT and warmer only. Not available with uplight option.

Optical Distributions



PS513001EN page 2
February 26, 2024 6:31 PM

FIXTURE TYPE: S1 AND S2

Table with columns: Project, Catalog #, Type, Prepared by, Notes, Date



McGraw-Edison GLEON Galleon

Area / Site Luminaire

Product Features

Product Certifications



Connected Systems

- WaveLinx
Enlighted

- Quick Facts
Lumen packages range from 4,200 - 80,800
(34W - 640W)
Efficacy up to 156 lumens per watt
Options to meet Bay American and other domestic preference requirements

Dimensional Details

Table with columns: Number of Light Sources, 'A' Width, 'B' Height, 'C' Depth, 'D' Mount Arm Length, 'E' Quick Mount Arm Length, 'F' Quick Mount Extended Arm Length



NOTES:
1. See McGraw-Edison.com for product details to confirm specifications. Not all product variations are D1C qualified.
2. DA Certified for 3000K CCT and warmer only.



PS500202EN page 1
June 14, 2022 5:43 PM

McGraw-Edison GLEON Galleon

Table with columns: Product Family, Configuration, Light Output, Color, Voltage, Distribution, Mounting, Finish


Table with columns: Product Family, Configuration, Light Output, Color, Voltage, Distribution, Mounting, Finish

- Notes:
1. See McGraw-Edison.com for product details to confirm specifications. Not all product variations are D1C qualified.
2. DA Certified for 3000K CCT and warmer only.
3. Not available with 0-10V dimming.
4. Only for use with 48V IP66 systems. For NEC, see use with underground systems, impedance grounded systems and other grounded systems (generally known as Three Phase Three Wire Delta, Three Phase High Leg Delta and Three Phase Corner Grounded Delta systems).
5. IP66 ambient operating temperature: 0°C to 50°C (32°F to 122°F), 0°C to 35°C (32°F to 95°F). Not available with 0-10V dimming in 0-10V systems.
6. Ambient operating temperature: 0°C to 50°C (32°F to 122°F), 0°C to 35°C (32°F to 95°F). UL94V-0 rated components.
7. Includes integral photonic.
8. Designed for use with Dim Mount and Decorative Pendant Mount only.
9. Designed for use with Decorative Pendant Mount only.
10. Not available with 0-10V dimming or compatible with MS/DM or LRM sensors.

Product Specifications

- Construction
Low profile, die-cast aluminum housing provides a clean, symmetric aesthetic
Greater than 90% lumen maintenance at 50,000 hours
IP66 rated
120-277V 50/60Hz, 347V 60Hz or 480V 60Hz operation
Five optical distributions utilizing visual comfort waveguide technology
10 lumen packages, ranging from 2,757 to 22,831
Integral uplight optics utilizes a dedicated, RW light engine, producing 300 lumens for reduced visual contrast and glare
IDA Certified for 3000K CCT and warmer only. Not available with uplight option.

Optical Distributions



PS500202EN page 2
June 14, 2022 5:43 PM

FIXTURE: S3 - S5

Table with columns: Project, Catalog #, Type, Prepared by, Notes, Date



McGraw-Edison GWC Galleon Wall

Wall Mount Luminaire

Product Features

Product Certifications



Connected Systems

- WaveLinx
Enlighted

- Quick Facts
Choice of thirteen high-efficiency, patented AccuLED Optics
Downward and inverted wall mounting configurations
Eight lumen packages from 3,215 up to 17,056
Efficacies up to 154 lumens per watt

Dimensional Details

Table with columns: Number of Light Sources, 'A' Width, 'B' Height, 'C' Depth, 'D' Mount Arm Length, 'E' Quick Mount Arm Length, 'F' Quick Mount Extended Arm Length



NOTES:
1. See McGraw-Edison.com for product details to confirm specifications. Not all product variations are D1C qualified.
2. DA Certified for 3000K CCT and warmer only.



PS500404EN page 1
December 5, 2021 5:13 PM

McGraw-Edison GWC Galleon Wall

Table with columns: Product Family, Configuration, Light Output, Color, Voltage, Distribution, Mounting, Finish


Table with columns: Product Family, Configuration, Light Output, Color, Voltage, Distribution, Mounting, Finish

- Notes:
1. See Light Connectors Qualified. Refer to www.designlights.org Qualified Products List under Family Models for details.
2. Only use with 48V IP66 systems. For NEC, see use with underground systems, impedance grounded systems and other grounded systems (generally known as Three Phase Three Wire Delta, Three Phase High Leg Delta and Three Phase Corner Grounded Delta systems).
3. Not available with 0-10V dimming.
4. Only for use with 48V IP66 systems. For NEC, see use with underground systems, impedance grounded systems and other grounded systems (generally known as Three Phase Three Wire Delta, Three Phase High Leg Delta and Three Phase Corner Grounded Delta systems).
5. IP66 ambient operating temperature: 0°C to 50°C (32°F to 122°F), 0°C to 35°C (32°F to 95°F). Not available with 0-10V dimming in 0-10V systems.
6. Ambient operating temperature: 0°C to 50°C (32°F to 122°F), 0°C to 35°C (32°F to 95°F). UL94V-0 rated components.
7. Includes integral photonic.
8. Designed for use with Dim Mount and Decorative Pendant Mount only.
9. Designed for use with Decorative Pendant Mount only.
10. Not available with 0-10V dimming or compatible with MS/DM or LRM sensors.

Product Specifications

- Construction
Low profile, die-cast aluminum housing provides a clean, symmetric aesthetic
Greater than 90% lumen maintenance at 50,000 hours
IP66 rated
120-277V 50/60Hz, 347V 60Hz or 480V 60Hz operation
Five optical distributions utilizing visual comfort waveguide technology
10 lumen packages, ranging from 2,757 to 22,831
Integral uplight optics utilizes a dedicated, RW light engine, producing 300 lumens for reduced visual contrast and glare
IDA Certified for 3000K CCT and warmer only. Not available with uplight option.

Optical Distributions



PS500404EN page 2
December 5, 2021 5:13 PM

C:\Users\unrussell\AppData\Local\Temp\AcPublish_21860\837-24117_Skyport_Hongars at Redfield - Elec.dwg

WARE MALCOLM
Leading Design for Commercial Real Estate
2777 E. Camelback Rd., Suite #325
Phoenix, AZ 85016
P. 480.767.1001

PROJECT NO: 250-PA-2024
KEY CODE: 53E64
OWNER/DEVELOPER:
Brian Regehr
480.355.4227
bregehr@wslgp.com

ARCHITECT:
WARE MALCOLM
Kevin Everham - Principal
2777 East Camelback Road #325
Scottsdale, Arizona 85016
480.800.5294
keverham@waremalcomb.com

SKYPORT AT REDFIELD
HANGARS
7600 E. REDFIELD RD
SCOTTSDALE, AZ 85260

Table with columns: DATE, REMARKS

Table with columns: PA / PM, DRAWN BY, JOB NO.

SHEET
052
7-DR-2024
8/08/2024