


### L01 - IN GROUND WALL WASH

#### AQUA DRUM™




Aqua Drum™ fixtures are high output, submersible heads suitable for use in all aquatic locations down to a depth of 20' (6m). A range of emitter types, lens options and full UL676 Pool & Spa certification make these heads particularly suited for exterior facade washing as well as fountain, pond and landscape applications.

Three size options, each with differing head diameters and emitter counts ensure that there is an Aqua Drum for every available space and throw distance. Optional in-grade housings are available for each Aqua Drum size to enable fully-sealed walk-over installations.

#### ACCLAIM LIGHTING

#### AT A GLANCE

**Optics**



15° x 15°  
15° x 25°  
15° x 35°  
25° x 25°  
45° x 45°  
60° x 60°  
90° x 90°

**Emitters**

Fixed or RGBW  
White (2700K, 3000K, 3500K or 4000K)  
RGBW (2700K or 4000K)

**Sizes**

EO (85.6" / 2183mm)  
SO (96.5" / 2453mm)  
HO (127.5" / 3238mm)

**Power** Low voltage: 24VDC via Aqua Driver

**Temperature** -40°F to 122°F / -40°C to 50°C

**Protection** Ingress: IP68 IK08

**Output** Up to 3,250 lumens

**Material** SAE 316 multienvironmental marine-grade stainless steel

#### CONFIGURE YOUR PRODUCT

AQP-261- N

Example final code: AQP-261-CKLN

### L02 - WALL SCONCE DOWN SPOT

#### HUNZA PURE OUTDOOR LIGHTING

### Pillar Pagoda Lite

PROJECT: \_\_\_\_\_  
TYPE: \_\_\_\_\_  
SOURCE: \_\_\_\_\_  
NOTES: \_\_\_\_\_

#### Adjustable Well Light

### SPJ-CBWL-16

#### PURELED SPECIFICATIONS

**PER END**

**LED Chip:** Cree XHP50-2 Plug and Play based on a 1000mA LED board

**Luminaire Output Per Head:** 170 Lumens @ 1200mA (4 watts), 340 Lumens @ 2000mA (8 watts), 160 Lumens @ 2000mA (4 watts), delivered from luminaires with unobstructed beam

**Lumens Per Watt:** 85 Lumens maximum @ 8 watts, delivered from luminaires with unobstructed beam

**CRI (900K):** 90+

**Color Temperatures:** 2700K, 3000K, 4000K

**Beam Angles:** 15, 25, 35, 60/300

**Ingress Protection:** IP60

**Warranty:** Electronics - 5 years  
Body Cap: 5 - 10 years  
Body Aluminum: 3 years

**Standards:** ANSI/IES RP-41, EN12468, IESNA E-18, IESNA E-20, IESNA E-21, IESNA E-22, IESNA E-23, IESNA E-24, IESNA E-25, IESNA E-26, IESNA E-27, IESNA E-28, IESNA E-29, IESNA E-30, IESNA E-31, IESNA E-32, IESNA E-33, IESNA E-34, IESNA E-35, IESNA E-36, IESNA E-37, IESNA E-38, IESNA E-39, IESNA E-40, IESNA E-41, IESNA E-42, IESNA E-43, IESNA E-44, IESNA E-45, IESNA E-46, IESNA E-47, IESNA E-48, IESNA E-49, IESNA E-50, IESNA E-51, IESNA E-52, IESNA E-53, IESNA E-54, IESNA E-55, IESNA E-56, IESNA E-57, IESNA E-58, IESNA E-59, IESNA E-60, IESNA E-61, IESNA E-62, IESNA E-63, IESNA E-64, IESNA E-65, IESNA E-66, IESNA E-67, IESNA E-68, IESNA E-69, IESNA E-70, IESNA E-71, IESNA E-72, IESNA E-73, IESNA E-74, IESNA E-75, IESNA E-76, IESNA E-77, IESNA E-78, IESNA E-79, IESNA E-80, IESNA E-81, IESNA E-82, IESNA E-83, IESNA E-84, IESNA E-85, IESNA E-86, IESNA E-87, IESNA E-88, IESNA E-89, IESNA E-90, IESNA E-91, IESNA E-92, IESNA E-93, IESNA E-94, IESNA E-95, IESNA E-96, IESNA E-97, IESNA E-98, IESNA E-99, IESNA E-100

#### PRODUCT CONFIGURATION

Cat. No. P1LPGLL

Please fill in appropriate codes into boxes provided

| Luminaire | Power | Material | Beam | Colour | Accessories |
|-----------|-------|----------|------|--------|-------------|
| P1LPGLL   |       |          |      |        |             |

**FINISHES:**  Matte Brass (MBR)  White (W)  Black (B)  Brush (BR)  Satin Brass (SB)  Aged Brass (AB)

**WARRANTY:**  5 Year (5Y)  3 Year (3Y)  1 Year (1Y)

**OTHER LAMP OPTIONS:** P1LPGLL - G4 LED Retrofit 12V Lamp (Steps vary by market - please refer to supplier for details)

### L03 - LANDSCAPE LIGHT

#### SPJ LIGHTING Inc. ARCHITECTURAL, LANDSCAPE & OUTDOOR LIGHTING

### Adjustable Well Light

### SPJ-CBWL-16

#### Adjustable Well Light

### SPJ-CBWL-16

**MODEL:** SPJ-CBWL-16  
**MATERIAL:** Solid Brass  
**FINISH:** Solid Brass  
**ELECTRICAL:** 8-15W, 12V, 18V, 120V  
**INGRESS PROTECTION:** IP20  
**OUTPUT:** 150 Lumens  
**COLOR TEMPERATURE:** 2700K  
**MOUNTING:** In Ground Niche

**FINISHES:**  Matte Brass (MBR)  White (W)  Black (B)  Brush (BR)  Satin Brass (SB)  Aged Brass (AB)

**WARRANTY:**  5 Year (5Y)  3 Year (3Y)  1 Year (1Y)

**OTHER LAMP OPTIONS:** SPJ-CBWL-16-58-2W-27K-8-15W

### L04 - LANTERN

#### CURREY & COMPANY

### Ledoux Lantern

90303-0407  
Sala

Overall: 25" x 20" x 20"  
Adjustable Height: 21" to 30"  
Finish: Black/Brass  
Materials: Wrought Iron / Steel

Net Weight: 10 lbs  
Number of Lights: 4  
Suggested Bulb: CA Flame Top  
Socket Type: E27  
Socket Power: 60/75/100

Chain Included: 0' Black/Brass  
Coat: 12' Black  
Shade: Off White Linen  
Shade Dimensions: 18.25" x 18.25"

#### Sign Light

### SPJ-WM1600

**MODEL:** SPJ-WM1600  
**MATERIAL:** Solid Brass  
**FINISH:** Solid Brass  
**ELECTRICAL:** 15W or 120V  
**INGRESS PROTECTION:** IP20  
**OUTPUT:** 2700K  
**MOUNTING:** Surface Canopy Niche

**FINISHES:**  Matte Brass (MBR)  White (W)  Black (B)  Brush (BR)  Satin Brass (SB)  Aged Brass (AB)  Raw Copper (RC)

**WARRANTY:**  5 Year (5Y)  3 Year (3Y)  1 Year (1Y)

**OTHER LAMP OPTIONS:** SPJ-WM1600-MBR-8W-27K-12V

### L05 - DECORATIVE STRING LIGHTS

#### tivoli

### 12V Litesphere™ ADAPT 2.0

Project: \_\_\_\_\_ Type: \_\_\_\_\_

- The next evolution of ADAPT delivers a robust specification-grade strand with factory molded standard spacing for consistent quality from start to finish
- Litesphere ADAPT 2.0 design provides optional suspended mounting or a twist-off cap for surface applications
- Available DunkSky option with colored light shade
- 12V DC Low voltage system for long runs
- Socket and cord color available in black or white
- Proprietary ADAPT screw base fitting
- Silicone-coated ADAPT glassware for assisting with shatter resistance
- IP67
- cULus
- 3 Year warranty

#### Adjustable Well Light

### SPJ-WM1600

**Dimensions:**

SHADES: 8.8K-10 10.2" H x 5.5" W (Weight: 0.7 lbs)

BULB NOT USED

7.1" x 6.7" x 2.375"

### L06 - SURFACE MOUNT DOWN LIGHT

#### ~CYLINDER IP66 Series

Full range of cylinders offered in round and square. 3 types of installation (pendant, surface and wall mount). IP66 Exterior Rated. Anti-glare design with low UGR <19 even for high output series. Low output has UGR <10 and shielding angle of 25 degree. High output has UGR <17 and shielding angle of 40 degree. High power range from 5W to 90W. Suitable for applications up to 60 feet. Custom wattages available. Certain sizes are available with internal emergency battery backup. Multiple installation options offered.

#### Sign Light

### SPJ-WM1600

**Specifications:**

Input Voltage: 100-277V AC  
Wattage: 10W - 90W  
Delivered Lumens: 800lm-7450lm  
Efficacy (LPW): 85-100lm/W  
CCT: 27K, 30K, 35K, 40K  
CRI: >90RA  
Beam Angle: 15°, 24°, 36°, 45°, 60°  
UGR: <19  
Dimming: Phase & 0-10V (100%-5%)  
Lamp Life: 50,000hrs  
Environment: IP20 & IP66  
Operating Temp: -4° F - 131° F  
Require with battery for operating temperatures of 40°C - 60°C

| Series | Mounting      | Shape | Suspension | Wattage | CCT     | Optic     | Accessories | Shell         | Reflector          |
|--------|---------------|-------|------------|---------|---------|-----------|-------------|---------------|--------------------|
| ACHES  | Pendant Mount | RD    | Round      | 10W-90W | 27K-40K | 15 Degree | HC          | Hexal Lower   | WH-White W-White   |
| RSR    | Surface Mount | SQ    | Square     | 10W-90W | 27K-40K | 24 Degree | LS          | Linear Spread | BL-Black B-Black   |
| SWR    | Surface Mount | SW    | Square     | 10W-90W | 27K-40K | 36 Degree | LS          | Linear Spread | SW-Silver C-Chrome |
| ACM    | Surface Mount | AC    | Circle     | 10W-90W | 27K-40K | 45 Degree | LS          | Linear Spread | G-Gold G-Gold      |
| AN     | Surface Mount | AN    | Annular    | 10W-90W | 27K-40K | 60 Degree | LS          | Linear Spread | N-Black Nickel     |

### L07 - WALL MOUNTED SITE AREA LIGHT

#### EXO LNC COMPACT LED LITERARY

FEATURES:

- Compact LNC LED is designed for perimeter illumination and available in 3 lumen packages for safety, security and clarity
- 3000K, 4000K, 5000K and Amber color temperatures
- Up to 41 spacing to mounting height ratio means fewer fixtures to install
- Adjustable diffuser included. Use for applications where entrance or location where reduced brightness is desired. (Maximum spacing with diffuser 30ft)
- Die-cast aluminum housing with decorative Laredo styling
- Full cut-off, non-glare, non-bleed-through
- Listed to UL 924 for use in wet locations

#### Sign Light

### SPJ-WM1600

**Specifications:**

Decorative die-cast aluminum housing and clear lens

Suggested design protects internal components and provides excellent thermal management for long life

Powder paint finishes provide lasting appearance in outdoor environments

Full cut-off distribution. Ambient diffuser included. Use for applications near entrances or locations where reduced brightness is desired

Optics: LNC-16, LNC-18, LNC-24, LNC-36, LNC-48, LNC-60, LNC-72, LNC-84, LNC-96, LNC-108, LNC-120, LNC-132, LNC-144, LNC-156, LNC-168, LNC-180, LNC-192, LNC-204, LNC-216, LNC-228, LNC-240, LNC-252, LNC-264, LNC-276, LNC-288, LNC-300

Installation: Quick mount adapter provides quick installation, designed for recessed box or square junction box

Electrical: 60000 hours minimum LED life at L86 rating per IESNA 90-311

Minimum operating temperature is -40°C/40°F

0-10V dimming 0-10V only

LNC-16, LNC-18, LNC-24, LNC-36, LNC-48, LNC-60, LNC-72, LNC-84, LNC-96, LNC-108, LNC-120, LNC-132, LNC-144, LNC-156, LNC-168, LNC-180, LNC-192, LNC-204, LNC-216, LNC-228, LNC-240, LNC-252, LNC-264, LNC-276, LNC-288, LNC-300

Controls: Photocell option is available to provide dusk-to-dawn control for additional energy savings

### L08 - WALL SCONCE SPOT LIGHT

#### ~CYLINDER IP66 Series

Full range of cylinders offered in round and square. 3 types of installation (pendant, surface and wall mount). IP66 Exterior Rated. Anti-glare design with low UGR <19 even for high output series. Low output has UGR <10 and shielding angle of 25 degree. High output has UGR <17 and shielding angle of 40 degree. High power range from 5W to 90W. Suitable for applications up to 60 feet. Custom wattages available. Certain sizes are available with internal emergency battery backup. Multiple installation options offered.

#### Sign Light

### SPJ-WM1600

**Specifications:**

Input Voltage: 100-277V AC  
Wattage: 10W - 90W  
Delivered Lumens: 800lm-7450lm  
Efficacy (LPW): 85-100lm/W  
CCT: 27K, 30K, 35K, 40K  
CRI: >90RA  
Beam Angle: 15°, 24°, 36°, 45°, 60°  
UGR: <19  
Dimming: Phase & 0-10V (100%-5%)  
Lamp Life: 50,000hrs  
Environment: IP20 & IP66  
Operating Temp: -4° F - 131° F  
Require with battery for operating temperatures of 40°C - 60°C